

# GVEV.R25111 - Swinging Fire Door Closers

## Swinging Fire Door Closers

[See General Information for Swinging Fire Door Closers](#)

### SUZHOU FUERDA INDUSTRY CO LTD

R25111

No 1 OUJIANG ROAD, SHUANGFENG

TAICANG

SUZHOU, JIANGSU 215416 CHINA

**Cam action concealed mounted type** Model(s) C6000+

**For self closing doors, without hold-open feature, cam action type, size 2-5** Model(s) C8000+

**For self closing doors, without hold-open feature, concealed mounted type** Model(s) F6203G+

**For self closing doors, without hold-open feature, concealed mounted type, size 3** Model(s) 1003-REC+

**For self closing doors, without hold-open feature, overhead concealed mounted type, size 2** Model(s) C1020+

**For self closing doors, without hold-open feature, overhead concealed mounted type, size 2-3** Model(s) C2013+

**For self closing doors, without hold-open feature, overhead concealed mounted type, size 2-4** Model(s) C2014+, F7325BC+

**For self closing doors, without hold-open feature, overhead concealed mounted type, size 2-5** Model(s) C2035+

**For self closing doors, without hold-open feature, overhead concealed mounted type, size 3** Model(s) C1030+

**For self closing doors, without hold-open feature, overhead concealed mounted type, size 4** Model(s) C1040+

**For self closing doors, without hold-open feature, overhead concealed mounted type, size 5** Model(s) C1050+

**For self closing doors, without hold-open feature, surface mounted type** Model(s) 504BC+, F1602BC+, F1703BC+, F1704BC+, F1705BC+, F1725BC+, F1726BC+, F1736BC+, MH-2431xCOV+

**For self closing doors, without hold-open feature, surface mounted type, size 2** Model(s) 430P+, B2W+, C52BC+, CL8202+, CL8203+, DYN-2000+, F8202+, F8500+, F8902+, MH-1077+, SARO DC2/3+

**For self closing doors, without hold-open feature, surface mounted type, size 2-3** Model(s) F8200+

**For self closing doors, without hold-open feature, surface mounted type, size 2-4** Model(s) 300PBFCOV+, 300PCOV+, 5009+, 514+, 7400+, 7500+, CL-3870ADA+, DC50-AL+, DC50-DU+, DC8900AL+, DC8900DU+, DYN-1614+, F1714+, F8900+, F8900BC+

**For self closing doors, without hold-open feature, surface mounted type, size 2-5** Model(s) 6115+, 9000+, CL-3870+, F8915BC+

**For self closing doors, without hold-open feature, surface mounted type, size 2-6** Model(s) 3000+, 3200+, 4001+, 4001CNS+, 4041+, 4116+, 416+, 8116+, 9000-PBC+, 9000-PBF+, 9000-PBF/DA+, 9000-PDA+, 9016+, 9116+, CL-4840+, CL8400BF+, CL8600BF+, CL8600BFDA+, CL8844BF+, CR441+, CR441DA+, CR801+, CR801S+, DC41-AL+, DC41-DU+, DC8300AL+, DC8300DU+, DC8400AL+, DC8400DU+, DC9000PBC/BF AL+, DC9000PBC/BF DUR+, DYN-4401+, DYN-8500+, DYN-9000+, F1916+, F8100+, F8300+, F8400+, F8416BC+, F8416DA+, F8916BC+, MH-2461 DELXCOV+, MH-2461XCOV+, MH-5041xCOV+, N900PBF+, N900PBFDA+, RGN900PBF+, SARO-BD 1-6+

**For self closing doors, without hold-open feature, surface mounted type, size 3** Model(s) 7200+, 7300+, 730P+, B3W+, C53BC+, CL-3353+, DYN-3000+, F1600+, F8503+, F8903+, J 4609\*\*+, J4611\*\*+

**For self closing doors, without hold-open feature, surface mounted type, size 3-6** Model(s) 1036+, DYN-1636+, F8936BC+

**For self closing doors, without hold-open feature, surface mounted type, size 4** Model(s) 4441+, B4W+, C54BC+, CL-3084+, CL-3354+, DYN-4000+, F8904BC+

**For self closing doors, without hold-open feature, surface mounted type, size 5** Model(s) 4551+, B5W+, C55BC+, F8905BC+

**For self closing doors, without hold-open feature, surface mounted type, size 6** Model(s) B6W+

+ - Also evaluated in accordance with Standard UL 10C, designed to be used with swinging type fire doors rated up to and including 3h.

Trademark and/or Tradename: "CRP", "FRD", "RAMCO"

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"